

Key Rubber Gasket for Flanges

Key rubber gasket for flanges made of EPDM rubber complying BSEN 681-1. All dimensions is designed in according to BSEN 1514-1 (formerly BS 4865:Part 1) as shown in the table below which is suitable for flanges and fittings complying with BSEN 1092 (formerly BS4504), BSEN 545 (formerly BS4772), BSEN 598 and BSEN 969. Gasket thickness are 1.5mm, 2mm, 3mm, 4mm & 5mm and non-standard size is available prior customers' order.



FF Type



IBC Type

Dimension of Gasket

Nominal Diameter	Outside Diameter for PN 16		Outside Diameter for PN 25		Outside Diameter for PN 40	
	FF Type	IBC Type	FF Type	IBC Type	FF Type	IBC Type
10	90	46	90	46	90	46
15	95	51	95	51	95	51
20	105	61	105	61	105	61
25	115	71	115	71	115	71
32	140	82	140	82	140	82
40	150	92	150	92	150	92
50	165	107	165	107	165	107
65	185	127	185	127	185	127
80	200	142	200	142	200	142
100	220	162	235	168	235	168
125	250	192	270	194	270	194
150	285	218	300	224	300	224
200	340	273	390	284	375	290
250	405	329	425	340	450	352
300	460	384	485	400	515	417
350	520	444	555	457	580	474
400	580	495	620	514	660	546
450	640	555	670	564	685	571
500	715	617	730	624	755	628
600	840	734	845	741	890	747

Remark: The above information may change without prior notice.